

## PNEUMATIC STEEL STRAPPING TOOL WITH WITH SEAL, UPCUT JOINT



### TECHNICAL SPECIFICATIONS

#### DIMENSIONS

Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	11.3 kgs • 25lbs

#### FEEDING

Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s - 25 cuft/min

#### PERFORMANCE

Max. tension force	9000 N - 15000 N 6 bar - 87 psi
Tensioning speed	4,5 mt/m @ 9000 N 4 mt/m @ 15000 N
Sealing	Seal double notches
Joint strength	80% of breaking strength*

\* variable according to strap type

### MODEL

CODE	TYPE	STRAP	THICKNESS
T511943	ITA 51-19mm-9000N- 3B	R 850N/mm <sup>2</sup>	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm <sup>2</sup>	0.63mm 0.025" - 0.8mm 0.031"
T512543	ITA 51-25mm-15000N- 3B	R 850N/mm <sup>2</sup>	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm <sup>2</sup>	0.63mm 0.025" - 0.8mm 0.031"
T513243	ITA 51-32mm-15000N- 3B	R 850N/mm <sup>2</sup>	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm <sup>2</sup>	0.63mm 0.025" - 0.8mm 0.031"

### SEAL DOUBLE NOTCHES

