

LOW PRESSURE PNEUMATIC STEEL STRAPPING TOOL WITH SEAL JOINT



TECHNICAL SPECIFICATIONS

DIMENSIONS

Length	430mm • 16.9"
Width	260mm • 10.2"
Height	310mm • 12.2"
Weight	11.3 kgs • 25lbs

FEEDING

Pressure range	5.5 -7 bar / 78 -99 psi
Air consumption	12 L/s - 25 cuft/min

PERFORMANCE

Max. tension force	7000 N 4,5 bar - 65 psi
	9000 N - 15000 N - 6,5 bar - 95 psi
Tensioning speed	12mt/m @ 7000 N
	5 mt/m @ 9000 N
	4 mt/m @ 15000 N
Sealing	Seal double notches
Joint strength	80% of breaking strength*

* variable according to strap type

MODEL

CODE	TYPE	STRAP	THICKNESS
T621943	ITA 62-19mm-9000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"
T622543	ITA 62-25mm-15000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"
T623243	ITA 62-32mm-15000N- 2B	R 850N/mm ²	0.6mm 0.024" - 1mm 0.039"
		R 1100N/mm ²	0.63mm 0.025" - 0.8mm 0.031"

SEAL DOUBLE NOTCHES

